


SF-M18/G120

445-460W

182±1.5×92.875±1.5mm

Cells 108



Bifacial Double Glass

N-Type Half-Cell Module

Max Power Out: 460W

Max Efficiency: 23.02%

Power Tolerance: 0~+5W



SMBB Technology

Better light trapping and current collection to improve module power output and reliability



PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and materials control.



Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance.



Reduced Hot Spot Loss

Optimized electrical design and lower operating current for reduced hot spot loss and better temperature coefficient.



Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal).




High Energy Generation, Low LCOE

Low Pmax temp coefficient increases energy production

Superior Warranty

- 15-year material & technology warranty
- 30-year linear power output warranty




Comprehensive Products and System Certificates

- IEC/EN61215-1:2021 & IEC/EN61215-2:2021
- IEC/EN61730-1:2016 & IEC/EN61730-2:2016
- UL61730-1:2017 & UL61730-2:2017
- UL61215-1:2017 & UL61215-2:2017
- IEC 61701:2020-Saltmist
- IEC 62716:2013-Ammonia
- IEC 62804:2020-PID
- IECCE Certificate Body (CB)
- UKCA:EN61730-2018
- ISO9001 & ISO14001 & ISO45001



Engineering Drawings



Structural Parameter

Dimensions of Module	1762×1134×30mm
Weight	24.5kg
Packing	37PCS/Pallet, 962PCS/40HQ
Front Glass	High Transparency Solar Glass 2.0mm
Back Glass	Heat Strengthened Glass 2.0mm
Frame	Black, Anodized Aluminium Alloy
J-Box	IP68 Rated
Cable	4.0mm ² , 300mm
Bypass Diodes	3PCS
Wind/ Snow Load	2400Pa/5400Pa
Connector	MC4 Compatible

Electrical Specification

(STC: Irradiance 1000W/m², Cell temperature 25°C, AM1.5G — NOCT: Irradiance 800W/m², Ambient temperature 20°C, Wind speed 1m/s)

Module Type	SF-M18/G120445		SF-M18/G120450		SF-M18/G120455		SF-M18/G120460	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax) [W]	445	333	450	337	455	341	460	344
Maximum Power Voltage (Vmp) [V]	33.51	32.08	33.69	32.26	33.87	32.43	34.07	32.60
Maximum Power Current (Imp) [A]	13.28	10.39	13.36	10.45	13.43	10.51	13.50	10.57
Open Circuit Voltage (Voc) [V]	38.97	37.32	39.17	37.51	39.37	37.70	39.57	37.89
Short Circuit Current (Isc) [A]	14.07	33.36	14.14	11.41	14.21	11.47	14.28	11.52
Module Efficiency [%]	22.27		22.52		22.77		23.02	
Cell Type [mm]	Mono 182±1.5×92.875±1.5, 108 Cells							
Operational Temperature [°C]	-40~+85°C							
Maximum System Voltage	1500V DC							
Max Series Fuse Rating	25A							

Electrical Characteristics With Different Power Bin (Reference to 10% Irradiance Ratio)

Total Equivalent Power (Pmax) [Wp]	489.50	495.00	500.50	506.00
Maximum Power Voltage (Vmp) [V]	33.51	33.69	33.87	34.07
Maximum Power Current (Imp) [A]	14.61	14.69	14.78	14.85
Open Circuit Voltage (Voc) [V]	38.97	39.17	39.37	39.57
Short Circuit Current (Isc) [A]	15.54	15.63	15.72	15.80
Irradiance Ratio (Rear/Front)	10%			

Temperature Ratings

Nominal Operating Cell Temperature	45±2°C
Temperature Coefficient of Isc	+0.05%/°C
Temperature Coefficient of Voc	-0.23%/°C
Temperature Coefficient of Pmax	-0.30%/°C

Curve Diagram

